



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

## ARDON® 4TIG

WELDING PROTECTION



TECHNICAL DATA



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

# ARDON® 4TIG

WELDING PROTECTION

## CODE

A2013

## MATERIAL

Palm  
Back  
Cuff  
Thickness  
goatskin leather (grey)  
goatskin leather (grey)  
cowsplit leather (soft, grey)  
0,7 – 1,0 mm (in palm)

## SIZE(S)

8 / M – 11 / 2XL

## UNIT

pair

## PACKING


Units in carton  
Units in polybag  
Retail packaging  
120 párů → 72 párů změna kartonáže v 5/2026  
12 pairs  
N/A

## DIMENSIONS

|                       | 5 | 6 | 7 | 8        | 9        | 10       | 11       | 12 |
|-----------------------|---|---|---|----------|----------|----------|----------|----|
| Carton H x W x D (cm) | - | - | - | 56x33x37 | 56x33x37 | 56x33x37 | 56x33x37 | -  |
| Carton (cbm)          | - | - | - | 0,0684   | 0,0684   | 0,0684   | 0,0684   | -  |

## WEIGHT

|             | 5 | 6 | 7 | 8     | 9     | 10    | 11    | 12 |
|-------------|---|---|---|-------|-------|-------|-------|----|
| Carton (kg) | - | - | - | 23,10 | 23,80 | 24,10 | 24,30 | -  |
| Unit (g)    | - | - | - | 180,8 | 186,7 | 189,2 | 190,8 | -  |



## Size chart (cm)

|                  | 5 | 6 | 7 | 8     | 9    | 10   | 11   | 12 |
|------------------|---|---|---|-------|------|------|------|----|
| Total length (A) | - | - | - | 34,0  | 34,5 | 35,5 | 37,0 | -  |
| Cuff length (B)  | - | - | - | 27,0  | 28,0 | 29,0 | 30,0 | -  |
| Cuff width (C)   | - | - | - | 15,0  | 15,0 | 15,0 | 15,0 | -  |
| Palm width (D)   | - | - | - | 11,75 | 12,0 | 12,8 | 13,3 | -  |

Tolerance (A) ± 0,50 (cm)

Tolerance (B) ± 0,50 (cm)

Tolerance (C) ± 0,50 (cm)

Tolerance (D) ± 0,50 (cm)

## DESCRIPTION

Full leather gloves made of goatskin and soft cowsplit leather with Kevlar seams.



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## STANDARDS

(EU) 2016/425

**EN ISO 21420:2020** Protective gloves – general requirements and test methods

**EN 388:2016 + A1:2018** Protective gloves against mechanical risks



### PROTECTION LEVELS

#### MECHANICAL RISKS

abrasion resistance  
 cut resistance  
 tearing resistance  
 puncture resistance  
 cut resistance acc. to ISO

#### LVL

2  
 1  
 2  
 2  
 X

#### score

500 – 2.000  
 1,2 – 2,5  
 25 – 50  
 60 – 100  
 not measured

#### unit

cycles  
 index  
 N  
 N  
 N

**EN 407:2020**

Protective gloves against heat or flame



### PROTECTION LEVELS

#### THERMAL RISKS

resistance to burning  
 resistance to contact heat  
 resistance to convectional heat  
 resistance to radiant heat  
 resistance to small drops of molten metals  
 resistance to large drops of molten metals

#### LVL

4  
 1  
 3  
 X  
 4  
 X

#### score

100°C for 15s  
 not measured  
 not measured

**EN 12477:2001:2001/A1:2005**

Protective gloves for welders

**TYP B**

### SPECIAL FEATURES

- welding gloves class B (TIG)
- leather of high and stable quality, every order submits to quality control and skin safety tests before loading (among others pH level and hexavalent chromium content are measured)
- full leather gloves with good mechanical abrasion resistance
- with Kevlar seams
- heat protection up to 100 ° C
- ARDON® design:
  - mandatory information on inner label
  - hi-viz manufacturer's logo



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

**Basic packaging (without sales label)**

A2013/08  
A2013/09  
A2013/10  
A2013/11

**EAN**

8592390116710  
8592390116727  
8592390116734  
8592390116741

TECHNICAL DATA