ARDON®
WORKWEAR
& OUTDOOR

ARDON®FIRLOW S3

SAFETY SHOES



DRY AIR

REFLECTIVE

WATER REPELLENT

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®FIRLOW S3

SAFETY SHOES



ARTICLE	**G3273/N**

MATERIAL

Upper	cowhide leather with SPLIT LEATHER design, hydrophobic treatment
Lining	MESH laminated breathable fabric
Sole	PU/PU, two-component spray coating, oil resistant, anti-static, antislip
Toe cap	steel
Plate	steel
Insole	BASIC
SIZE	35-50
UNIT	pair

PACKAGE

Units in a carton	10 pairs
Units in a box	1 pair

DIMENSIONS	35-42	43-46	47-50
Carton H x W x D (cm)	59,5 x 32,5x 37,5	62 x 34,5 x 39,5	62 x 36 x 41,5
Carton (cbm)	0,0725	0,0845	0,0926

Size EUR	**35**	**36**	**37**	**38**	**39**	**40**	**41**	**42**	**43**	**44**	**45**	**46**	**47**	**48**	**49**	**50**	**51**
Insole length mm	232	239	246	252	259	266	272	279	286	292	299	306	312	319	326	332	-
Foot length cm	22,7	23,4	24,1	24,7	25,4	26,1	26,7	27,4	28,1	28,7	29,4	30,1	30,7	31,4	32,1	32,7	-

DESCRIPTION

Safety low shoes with two-component polyurethane soles with a steel safety toe cap and a puncture-resistant insole. It has a hydrophobic treatment.

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

NORMS

(EU) 2016/425
EN ISO 20345:2022+A1:2024 Personal protective equipment - Safety footwear

Category S3 SR FO

Categories	**EN ISO 20345**	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	SR
WPA - upper resistant to water	✓	WPA
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
The shoes do not contain metal parts		0% METAL
HRO - resistance to contact heatup to 300 °C		300 °C
HI-insulation of the bottom of the shoe against heat		HI
CI-insulation of the bottom of the shoe against the cold		CI
Splatters of molten metal		WG
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		ESD
-		
-		
-		

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3273/35/N	8592390148193	13.62	1.362
G3273/36/N	8592390148209	13.65	1.365
G3273/37/N	8592390148216	13.69	1.369
G3273/38/N	8592390148223	13.72	1.372
G3273/39/N	8592390148230	13.75	1.375
G3273/40/N	8592390148247	13.79	1.379
G3273/41/N	8592390148254	13.85	1.385
G3273/42/N	8592390148261	13.91	1.391
G3273/43/N	8592390148278	13.92	1.392
G3273/44/N	8592390148285	13.95	1.395
G3273/45/N	8592390148292	13.98	1.398
G3273/46/N	8592390148308	14.01	1.401
G3273/47/N	8592390148315	14.15	1.415
G3273/48/N	8592390148322	14.25	1.425
G3273/49/N	8592390148339	14.30	1.430
G3273/50/N	8592390148346	13.50	1.350



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR







© ARDON s.r.o. / ALL RIGHTS RESERVED