



ARDON®
WORKWEAR
& **OUTDOOR**

ARDON® BRIMWIN S3S ESD

SAFETY SHOES



**WATER
REPELLENT**



REFLECTIVE



WINTER



NONMETALLIC



ESD

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® BRIMWIN S3S ESD

SAFETY SHOES

ARTICLE

G3515

MATERIAL

Upper

Suede microfiber/Oxford textile

Lining

3M Thinsulate insulation

Sole

PU/PU, dual-density injection

Toe cap

Fibreglass

Plate

Kevlar

Insole

Three-layer warm insole (Velvet/foam/felt)

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton

10 pairs

Units in a box

1 pair

DIMENSIONS

36-42

43-48

Carton H x W x D (cm)

34 x 45,5 x 62

37,5 x 47,5 x 64,5

Carton (cbm)

0,0959

0,1149

Size EUR

36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51

Insole length mm

240 247 253 260 267 273 280 287 293 300 307 313 320

Foot length cm

23,5 24,2 24,8 25,5 26,2 26,8 27,5 28,2 28,8 29,5 30,2 30,8 31,5

DESCRIPTION

Safety ankle footwear with a suede microfiber upper combined with durable Oxford textile. Insulation with a branded 3M Thinsulate lining ensures excellent thermal insulation in adverse winter conditions. Outsole made of dual-density injected PU/PU with anti-slip properties. Toe protection is provided by a fiberglass toe cap, while a non-metallic Kevlar midsole protects against punctures. Anatomical three-layer warm insole with a shock-absorbing construction.

NORMS

(EU) 2016/425

EN ISO 20345:2022+A1:2024

EN IEC 61340-4-3:2018

Personal protective equipment – Safety footwear
Electrostatics: Standard test methods for specific application – Footwear

Category

S3S CI FO SR ESD

Categories

EN ISO 20345

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SR - resistance to slipping on ceramic floor tiles with SLS
and on steel floors with glycerin

✓



WPA - water penetration and absorption

✓



Safety toe cap for toe protection

✓



P - resistance to punctures (protective insole)

✓



The shoes do not contain metal parts

✓



HRO - resistance to contact heatup to 300 °C



HI-insulation of the bottom of the shoe against heat



CI-insulation of the bottom of the shoe against the cold

✓



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can
be used on EPA premises

✓



-

-

-



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3515/36	8592390405036	13,75	1,375
G3515/37	8592390405043	14,05	1,405
G3515/38	8592390405050	14,26	1,426
G3515/39	8592390405067	14,5	1,45
G3515/40	8592390405074	14,68	1,468
G3515/41	8592390405081	14,9	1,49
G3515/42	8592390405098	15,104	1,5104
G3515/43	8592390405104	15,31	1,531
G3515/44	8592390405111	15,56	1,556
G3515/45	8592390405128	15,85	1,585
G3515/46	8592390405135	16,01	1,601
G3515/47	8592390405142	16,21	1,621
G3515/48	8592390405159	16,44	1,644



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

