ARDON®
WORKWEAR
& OUTDOOR

ARDON®BRIMWIN S3S ESD

SAFETY SHOES

TECHNICAL SHEET



WATER REPELLENT

REFLECTIVE

WINTER

0% METAL
NONMETALLIC

ESD
ESD

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®BRIMWIN S3S ESD

SAFETY SHOES



ARTICLE	**G3515**
MATERIAL	
Upper	Suede microfiber/Oxford textile
Lining	3M Thinsulate insulation
Sole	PU/PU, dual-density injection
Toe cap	Fibreglass
Plate	Kevlar
Insole	Three-layer warm insole (Velvet/foam/felt)
SIZE	36-48
UNIT	pair
PACKAGE	
Units in a carton	10 pairs
Units in a box	1 pair

DIMENSIONS	36-42	43-48
Carton H x W x D (cm)	34 x 45,5 x 62	37,5 x 47,5 x 64,5
Carton (cbm)	0,0959	0,1149

Size EUR	**36**	**37**	**38**	**39**	**40**	**41**	**42**	**43**	**44**	**45**	**46**	**47**	**48**	**49**	**50**	**51**
Insole length mm	240	247	253	260	267	273	280	287	293	300	307	313	320			
Foot length cm	23,0	23,7	24,3	25,0	25,7	26,3	27,0	27,7	28,3	29,0	29,7	30,3	31,0			

DESCRIPTION

Safety ankle footwear with a suede microfiber upper combined with durable Oxford textile. Insulation with a branded 3M Thinsulate lining ensures excellent thermal insulation in adverse winter conditions. Outsole made of dual-density injected PU/PU with anti-slip properties. Toe protection is provided by a fiberglass toe cap, while a non-metallic Kevlar midsole protects against punctures. Anatomical three-layer warm insole with a shock-absorbing construction.

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

NORMS

(EU) 2016/425
EN ISO 20345:2022+A1:2024 Personal protective equipment –Safety footwear
EN IEC 61340-4-3:2018 Electrostics: Standard test methods for specific application – Footwear

Category S3S CI FO SR ESD

Categories	**EN ISO 20345**	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	SR
WPA - water penetration and absorption	✓	WPA
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
The shoes do not contain metal parts	✓	0% METAL
HRO - resistance to contact heatup to 300 °C		300 °C
HI-insulation of the bottom of the shoe against heat		HI
CI-insulation of the bottom of the shoe against the cold	✓	CI
Splatters of molten metal		WG
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓	ESD
-		
-		
-		

TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3515/36	8592390405036	13,75	1,375
G3515/37	8592390405043	14,05	1,405
G3515/38	8592390405050	14,26	1,426
G3515/39	8592390405067	14,5	1,45
G3515/40	8592390405074	14,68	1,468
G3515/41	8592390405081	14,9	1,49
G3515/42	8592390405098	15,104	1,5104
G3515/43	8592390405104	15,31	1,531
G3515/44	8592390405111	15,56	1,556
G3515/45	8592390405128	15,85	1,585
G3515/46	8592390405135	16,01	1,601
G3515/47	8592390405142	16,21	1,621
G3515/48	8592390405159	16,44	1,644



© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz

ARDON®
WORKWEAR
& OUTDOOR



© ARDON s.r.o. / ALL RIGHTS RESERVED

ARDON®
WORKWEAR
& OUTDOOR







TECHNICAL SHEET

© ARDON s.r.o. / ALL RIGHTS RESERVED
ARDON s.r.o. tř. Kosmonautů 1221/2a, Olomouc www.ardon.cz